

United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE		FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO	
10/735,730	12/16/2003		Moo Yeol Park	8734.049 C1	3685	
30827	7590	06/28/2006		EXAMINER		
		& ALDRIDGE LL	CANNING, ANTHONY J			
1900 K STR WASHING		20006	ART UNIT	PAPER NUMBER		
	, – •		2879			

DATE MAILED: 06/28/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

		Applicati	on No.	Applicant(s)	
		10/735,7	/735,730 PARK ET AL.		
	Office Action Summary	Examine	7	Art Unit	
		Anthony .	J. Canning	2879	
Period fo	- The MAILING DATE of this commun	ication appears on th	e cover sheet with the c	orrespondence ad	ddress
A SHO WHIC - Exten after: - If NO - Failur Any ro	DRTENED STATUTORY PERIOD F HEVER IS LONGER, FROM THE M sions of time may be available under the provisions SIX (6) MONTHS from the mailing date of this comm period for reply is specified above, the maximum st e to reply within the set or extended period for reply ply received by the Office later than three months a d patent term adjustment. See 37 CFR 1.704(b).	IAILING DATE OF The of 37 CFR 1.136(a). In no evalunication, atutory period will apply and will, by statute, cause the approximation.	HIS COMMUNICATION ent, however, may a reply be tin rill expire SIX (6) MONTHS from blication to become ABANDONE	N. nely filed the mailing date of this o D (35 U.S.C. § 133).	
Status					
2a)☐ 3)☐	Responsive to communication(s) file This action is FINAL . Since this application is in condition closed in accordance with the practi	2b)⊠ This action is r for allowance except	for formal matters, pro		e merits is
Dispositio	on of Claims				
5) □ 6) ⊠ 7) □ 8) □ Application 9) □ □	Claim(s) 1-18 is/are pending in the above claim(s) is/a Claim(s) is/are allowed. Claim(s) 1-18 is/are rejected. Claim(s) is/are objected to. Claim(s) is/are objected to. Claim(s) are subject to restrict on Papers The specification is objected to by the drawing(s) filed on is/are: Applicant may not request that any objected to an including	etion and/or election relection and/or election relection relection relection relection relection relection to the drawing(s) becomes the drawing(s) because the	equirement. objected to by the location in abeyance. See	e 37 CFR 1.85(a).	FR 1.121(d).
11) 🔲 🗆	The oath or declaration is objected to	b by the Examiner. No	ote the attached Office	Action or form P	TO-1 52 .
12)[/ a)[Acknowledgment is made of a claim All b) Some * c) None of: 1. Certified copies of the priority 2. Certified copies of the priority 3. Copies of the certified copies application from the Internationee the attached detailed Office action	documents have bee documents have bee of the priority documental Bureau (PCT Rul	en received. en received in Applicati ents have been receive e 17 2(a)).	on No ed in this National	Stage
2) 🔲 Notice 3) 🔲 Inform	(s) of References Cited (PTO-892) of Draftsperson's Patent Drawing Review (Feation Disclosure Statement(s) (PTO-1449 or No(s)/Mail Date		4) Interview Summary Paper No(s)/Mail Do 5) Notice of Informal P 6) Other:	ate	O-152)

Art Unit: 2879

DETAILED ACTION

Request for Continued Examination

1. The request for continued examination of the instant application was entered on 10 May 2006.

Claim Rejections - 35 USC § 102

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

- (b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.
- 3. Claims 1-5, 11, 14, and 16-18 are rejected under 35 U.S.C. 102(b) as being anticipated by Nishino et al. (U.S. 6,010,384).
- 4. As to claim 1, Nishino et al. disclose a method for fabricating a liquid crystal display panel, including: forming a UV sealant on either one of first and second substrates (column 5, lines 44-46); forming a liquid crystal layer between the first and second substrates (column 1, lines 25-28); attaching the first and second substrates (column 1, lines 23-25); hardening the UV sealant other than the UV sealant on the regions where the UV sealant and at least one scribing line are crossed by irradiating a UV ray on the attached substrates (column 5, lines 44-46; the entire substrate is coating with UV sealant, therefore the regions with UV sealant where the UV sealant and the scribing lines don't cross will be hardened) with masking regions (column 5,

Art Unit: 2879

lines 47-48; UV rays irradiate the ultraviolet curing resin to expose the desired shape) where the UV sealant and at least one scribing line are crossed (column 1, lines 34-36; column 5, lines 44-46; the ultraviolet curing resin covers the entire substrate, the scribing lines are drawn onto the substrate, therefore the UV sealant and the scribing line cross), wherein the UV sealant on the regions where the UV sealant and at least one scribing line are crossed is not entirely cured (column 5, lines 44-52; because the mask allows the sealant to be hardened only in the display area, and the scribing lines are external to the display area, the sealant in the scribing lines will not be cured) and cutting the bonded substrates into a plurality of unit cells (column 1, lines 40-47).

- 5. As to claim 2, Nishino et al. disclose the method of claim 1, wherein the masking regions in the irradiating a UV ray on the attached substrates includes masking upper and lower side portions of the crossed regions between the UV sealant and the scribing line (column 5, lines 36-52; photomasks are used to expose a desired shape).
- 6. As to claim 4, Nishino et al. disclose the method of claim 1, wherein the masking regions in the irradiating a UV ray on the attached substrates includes masking an active region in addition to masking upper and lower side portions of the crossed regions between the UV sealant and the scribing lines (column 5, lines.
- 7. As to claims 3 and 5, Nishino et al. disclose the method of claims 1 and 4, wherein the masking regions in the irradiating a UV ray on the attached substrates includes masking left and right side portions of the crossed regions between the UV sealant and the scribing lines (see Fig. 5, items 102; column 7, lines 24-28; column 4, line 10).

Art Unit: 2879

8. As to claim 11, Nishino et al. disclose the method of claim 1, wherein the UV sealant includes one of monomer and oligomer each having both ends coupled to an acrylic group (column 5, lines 44-46; Nishino et al. disclose an acrylic resin as the UV sealant).

- 9. As to claim 14, Nishino et al. disclose the method of claim 1, wherein the scribing line is formed on the bonded substrates (column 7, lines 17-28).
- 10. As to claim 16, Nishino et al. disclose the method of claim 1, further including forming at least one column spacer on the first substrate (column 1, lines 49-53; although the second substrate is specified, the second substrate could just as easily be labeled the first substrate).
- 11. As to claim 17, Nishino et al. disclose the method of claim 1, wherein forming a liquid crystal layer includes dropping at least one droplet of liquid crystal onto either one of the first and second substrates (column 8, lines 50-54; because the liquid crystal material is injected droplets will be on either the first or second substrate).
- 12. As to claim 18, Nishino et al. disclose the method of claim 17, wherein the UV sealant is formed on the first substrate, and the at least one droplet of liquid crystal is dropped onto the second substrate (column 1, lines 49-53; column 8, lines 50-54; the spacers are formed on one substrate and then the substrates are bonded, the liquid crystal material is injected between the two of substrates; therefore liquid crystal material will be on the second substrate).

Claim Rejections - 35 USC § 103

13. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person

Art Unit: 2879

having ordinary skill in the art to which the subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

- 14. Claims 6-10, 12 and 13 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishino et al. (U.S. 6,010,384) in view of Takahara et al. (U.S. 5,426,522).
- 15. As to claim 6, Nishino et al. disclose the method of claim 1. Nishino et al. fail to disclose that the main sealant is a UV setting sealant.

Takahara et al. disclose the method of fabricating a liquid crystal display including a main sealant made of an ultraviolet setting material (column 5, lines 30-33). Takahara et al. further disclose that using a ultraviolet setting sealant is preferable because when the sealant is irradiated with UV radiation, only the resin material react and the liquid crystal phase is separated from the resin phase.

Therefore, it would have been obvious to one having ordinary skill in the art, at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the main sealant surrounding the display cell can be cured by ultraviolet radiation, as raught by Takahara et al., for the added benefit of having only the resin material react and the liquid crystal phase is separated from the resin phase.

- 16. As to claim 7, Nishino et al. and Takahara et al. disclose the method of claim 6, further masking an active region inside the main sealant (column 5, lines 44-46; the ultraviolet curing resin is coated on the overall surface of the substrate; therefore, the active region will be surrounded by some ultraviolet curing resin).
- 17. As to claim 8, Nishino et al. and Takahara et al. disclose the method of claim 6. Nishino et al. teach that the UV sealant forms at an outside of the main sealant (column 5, lines 44-46;

Art Unit: 2879

because the UV sealant is coated on the overall surface of the substrate, the UV sealant will be outside of the main sealant).

18. As to claim 9, Nishino et al. and Takahara et al. disclose the method of claim 6. Takahara et al. further disclose that the ultraviolet sealant includes one of monomer and oligomer each having both ends coupled to an acrylic group (column 5, lines 33-35). Takahara et al. further disclose that this sealant is preferable because when the sealant is irradiated with UV radiation, only the resin material react and the liquid crystal phase is separated from the resin phase.

Therefore, it would have been obvious to one having ordinary skill in the art. at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the main sealant surrounding the display cell is UV curable and made of a monomer or string of monomers having ends coupled to an acrylic group, as taught by Nishino et al., for the added benefit of having only the resin material react and the liquid crystal phase is separated from the resin phase.

19. As to claim 10, Nishino et al. and Takahara et al. disclose the method of claim 6. Takahara et al. further disclose that the main UV scalant includes one of monomer and oligomer each having one end coupled to an acrylic group and the other end coupled to an epoxy group (column 5, lines 41-49; various epoxy acrylates are give, such as 2-hydroxyethyl acrylate). Takahara et al. further discloses that this scalant is preferable because when the scalant is irradiated with UV radiation, only the resin material react and the liquid crystal phase is separated from the resin phase.

Application/Control Number: 10/735,730

Art Unit: 2879

Therefore, it would have been obvious to one having ordinary skill in the art. at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the main sealant surrounding the display cell is UV curable and made of a monomer or string of monomers having ends coupled to an acrylic group and an epoxy, as taught by Takahara et al., for the added benefit of having only the resin material react and the liquid crystal phase is separated from the resin phase.

20. As to claim 12, Nishino et al. disclose the method of claim 1. Nishino et al. fail to disclose that the UV scalant includes one of monomer and oligomer each having one end coupled to an acrylic group and the other end coupled to an epoxy group.

Takahara et al. further disclose that the main UV sealant includes one of monomer and oligomer each having one end coupled to an acrylic group and the other end coupled to an epoxy group (column 5, lines 41-49; various epoxy acrylates are give, such as 2-hydroxyethyl acrylate). Takahara et al. further discloses that this sealant is preferable because when the sealant is irradiated with UV radiation, only the resin material react and the liquid crystal phase is separated from the resin phase.

Therefore, it would have been obvious to one having ordinary skill in the art. at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the main sealant surrounding the display cell is UV curable and made of a monomer or string of monomers having ends coupled to an acrylic group and an epoxy, as taught by Takahara et al., for the added benefit of having only the resin material react and the liquid crystal phase is separated from the resin phase.

Art Unit: 2879

21. As to claim 13, Nishino et al. disclose the method of claim 1, further including heating the UV ray irradiated substrates with masking crossed regions between the UV sealant and the scribing lines (see Fig. 5, items 102, CSL-4, CSL-5, ASL-1, ASL-2; column 5, lines 47-48). Nishino et al. fail to disclose that the UV sealant includes one of monomer and oligomer each having one end coupled to an acrylic group and the other end coupled to an epoxy group.

Takahara et al. further disclose that the main UV sealant includes one of monomer and oligomer each having one end coupled to an acrylic group and the other end coupled to an epoxy group (column 5, lines 41-49; various epoxy acrylates are give, such as 2-hydroxyethyl acrylate). Takahara et al. further discloses that this sealant is preferable because when the sealant is irradiated with UV radiation, only the resin material react and the liquid crystal phase is separated from the resin phase.

Therefore, it would have been obvious to one having ordinary skill in the art. at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the main sealant surrounding the display cell is UV curable and made of a monomer or string of monomers having ends coupled to an acrylic group and an epoxy, as taught by Takahara et al., for the added benefit of having only the resin material react and the liquid crystal phase is separated from the resin phase.

22. Claim 15 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishino et al. (U.S. 6,010,384) in view of Bergeron et al. (U.S. 5,897,414).

Art Unit: 2879

23. As to claim 15, Nishino et al. disclose the method of claim 1. Nishino et al. fail to disclose that the cutting the bonded substrates into a plurality of unit cells is performed by scribing and breaking simultaneously.

Bergeron et al. disclose a method of cutting a display device using a laser, which will cause a simultaneous cut and break (column 10, lines 59-61). Using a technique to simultaneously cut and break the display device leads to a quicker production of the display device.

Therefore, it would have been obvious to one having ordinary skill in the art. at the time the invention was made, to modify the method of fabricating a liquid crystal display panel of Nishino et al. to include that the steps of cutting and breaking the display device is done simultaneously, as taught by Bergeron et al., for the added benefit of a more rapid production of the display device.

Response to Arguments

- 24. The examiner acknowledges the amendment to claim 1.
- 25. Regarding claim 1, Nishino (U.S. 6,010.384) disclose in column 5, lines 44-46 that the UV sealant is on the entire second substrate. A mask is used to cure a portion of the sealant in the display area, the scribing lines are external to the display portion. Therefore, the sealant in the scribing lines will not be cured since only the sealant in the display area is cured.

Art Unit: 2879

Contact Information

26. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Anthony J. Canning whose telephone number is (571)-272-2486. The examiner can normally be reached on M-F 8:00-4:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nimesh D. Patel can be reached on (571)-272-2457. The fax phone number for the organization where this application or proceeding is assigned is 703-872-9306.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Anthony Canning (W

21 June 2006

NIMESHKUMAR D. PATEL
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2800